

## Safety Data Sheet

### Inject-TITE™ FS™ Fast-Set

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

#### 1. Product and Company Identification

**ProductName:** Inject-TITE FS Fast-Set (Part A)

**Product Use:** Anchoring & Doweling

**CompanyIdentification:**

Wej-It® High-Performance Anchors®

110 Richards Avenue

Norwalk, CT 06854

Contact Phone: 1.203.857.2200

**Emergency Phone:**

Infotrac:

1.800.535.5053 (24hrs)

1.353.323.3500 (outside US)

#### 2. Hazards Identification (Part A)

**GHS Classification**

Health	Physical	Environmental
Skin Irritant Cat 2 Eye Irritant Cat 2A Skin Sens Cat 1	Not Classified	Toxic to Aquatic Life Cat-2

GHS Label:

**Warning:**



Causes eye irritation

Skin irritant

May cause skin sensitization

**Emergency Overview**

May cause skin sensitization

Avoid contact with the skin and eyes

Avoid breathing fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Use outdoors or in a well-ventilated area

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible dust hazard).

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible silica dust hazard).

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

---

**3. Composition/ Information on Ingredients (Part A)**

<b>CAS Number</b>	<b>Content %</b>	<b>Chemical Name</b>
25085-99-8	30 - 60	Diglycidyl Ether of Bisphenol A
14808-60-7	5 - 15	Crystalline Silica (quartz)
13463-67-7	1 - 5	Titanium Dioxide
Proprietary	10 - 20	Non - Hazardous Proprietary Ingredients
68460-21-9	7 - 15	Trimethylol Ethane Triglycidyl Ether
107-21-1	1 - 5	Ethylene Glycol (Cartridge ONLY)

---

**4. First Aid Measures (Part A)**

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

---

**5. Fire Fighting Measures (Part A)**

Flash Point: N/D

Flammable Limits: N/D

**Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard**

None known. Thermal decomposition can be formed.

**Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

---

**6. Accidental Release Measures (Part A)****Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions:**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

---

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

**7. Handling and Storage (Part A)**

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

**8. Exposure Control and Personal Protection (Part A)****Exposure Guidelines**

Component	CAS#	OSHA PEL	TLV
Ethylene Glycol (Cartridge ONLY)	107-21-1	50ppm (Ceiling)	100 mg/ m <sup>3</sup> (Ceiling)
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>
Titanium Dioxide	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

**Personal Protective Equipment****Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin / Body Protection**

Wear suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

**9. Physical and Chemical Properties (Part A)**

Appearance:	White Paste
Evaporation Rate:	N/A
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity (H <sub>2</sub> O=1):	1.4
Vapor Density (air = 1):	Non-Volatile
Vapor Pressure:	N/A
VOC Content:	See section 9 of part B for VOC content

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

pH:	N/D
Boiling Point:	N/A

---

**10. Stability and Reactivity (Part A)**

Stability:	Stable.
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents.
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

**11. Toxicological Information (Part A)****Acute Oral Toxicity:**  
Not Determined**Acute Dermal Toxicity:**  
Not Determined**Acute Inhalation Toxicity:**  
Not Determined**Skin Irritation:**  
Irritating to skin.  
The product has not been tested. The statement has been derived from the properties of the individual components.**Eye Irritation:**  
Irritating to eyes.  
The product has not been tested. The statement has been derived from the properties of the individual components.**Respiratory Irritation:**  
Inhalation of vapors or mists may cause irritation to the respiratory system.**Sensitization:**  
May cause allergic skin reaction and irritation to the respiratory system.  
The product has not been tested. The statement has been derived from the properties of the individual components.**Carcinogenicity Classification:**  
**Quartz Silica Sand (Crystalline Silica):**  
IARC Group1: Known human carcinogen based on human evidence.  
NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.  
**Titanium dioxide:**  
IARC Group2B: Possibly carcinogenic to humans.

## Safety Data Sheet

### Inject-TITE™ FS™ Fast-Set

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

## 12. Ecological Information (Part A)

### Acute Toxicity for:

#### Fish:

Diglycidyl Ether of Bisphenol A:

Fathead minnow/LC50 (96hrs): >3.1mg/l

#### Aquatic Invertebrates:

Diglycidyl Ether of Bisphenol A:

Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

#### Algae:

No Data Available

#### Microorganisms:

Diglycidyl Ether of Bisphenol A:

Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

#### Mobility:

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

---

## 13. Disposal Considerations (Part A)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

## 14. Transportation Information (Part A)

This product is not regulated as a hazardous material for transportation.

---

## 15. Regulatory Information (Part A)

HMIS Rating	
Health	*2
Flammability	1
Physical Hazard	0
PPE	B

### NFPA Rating



Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

**Federal Regulations****CERCLA RQ**

5000 lbs

**CAS**

107-21-1

**Chemical Name**

Ethylene Glycol (Cartridge ONLY)

SARA Title 311/312

Chronic Health Hazard

CA Prop 65

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

TSCA

Listed

**State Regulations:****State RTK**

NJ, MA, PA

**CAS#**

25085-99-8

107-21-1

14808-60-7

13463-67-7

**Chemical Name**

Diglycidyl Ether of Bisphenol A

Ethylene Glycol (Cartridge ONLY)

Crystalline Silica (quartz)

Titanium Dioxide

**16. Other Information (Part A)**

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard.

To the best of our knowledge, the information contained herein is accurate. However, Mechanical Plastics Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.

## Safety Data Sheet

### Inject-TITE™ FS™ Fast-Set

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

#### 1. Product and Company Identification

**ProductName:** Inject-TITE FS Fast-Set (Part B)

**Product Use:** Anchoring & Doweling

**Company Identification:**

Wej-It® High-Performance Anchors®

110 Richards Avenue

Norwalk, CT 06854

Contact Phone: 1.203.857.2200

**Emergency Phone:**

Infotrac:

1.800.535.5053 (24hrs)

1.353.323.3500 (outside US)

#### 2. Hazards Identification (Part B)

**GHS Classification**

Health	Physical	Environmental
Skin Corrosion Cat 1 Serious Eye Damage Cat 1 Skin Sen 1 Reproductive Tox Cat 2 Acute Tox Oral Cat 4 Acute Tox Inhalation Cat 4	Not Classified	Toxic to Aquatic Life Cat-2

GHS Label:

**Danger:**



Corrosive to skin and eyes



May cause skin sensitization  
Harmful if swallowed or inhaled



Reproductive toxicity

**Emergency Overview**

Causes skin burns

Causes severe eye damage

Harmful if swallowed or inhaled

May cause skin sensitization

Suspected of damaging fertility

Wash skin thoroughly after handling

Avoid breathing fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Use outdoors or in a well-ventilated area

Avoid contact during pregnancy/while nursing

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible silica dust hazard)

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

**3. Composition/ Information on Ingredients (Part B)**

<u>CAS Number</u>	<u>Content %</u>	<u>Chemical Name</u>
140-31-8	5 – 15	n-aminoethylpiperazine
84852-15-3	15 – 30	Nonylphenol
90-72-2	3 – 7	Tris-2, 4, 6(dimethylaminomethyl) phenol
100-51-6	1 – 5	Benzyl Alcohol
68953-36-6	5 – 15	Polyamido Amine (Bulk ONLY)
68082-29-1	5 – 15	Liquid polyamido resin (Cartridge ONLY)
14808-60-7	25 – 40	Crystalline Silica (quartz)
107-21-1	0.1– 1	Ethylene Glycol (Cartridge ONLY)

**4. First Aid Measures (Part B)**

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

**5. Fire Fighting Measures (Part B)**

Flash Point: N/D

Flammable Limits: N/D

**Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard**

None known. Thermal Decomposition can be formed.

**Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.



**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

**6. Accidental Release Measures (Part B)****Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

**7. Handling and Storage (Part B)**

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

**8. Exposure Control and Personal Protection (Part B)****Exposure Guidelines**

Component	CAS#	OSHA PEL	TLV
Ethylene Glycol (Cartridge ONLY)	107-21-1	50ppm (Ceiling)	100 mg/ m <sup>3</sup> (Ceiling)
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

**Personal Protective Equipment****Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye / Face Protection**

Wear splash proof chemical goggles/full face shield if there is a potential for splashing.

**Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

---

**9. Physical and Chemical Properties (Part B)**

Appearance:	Black Paste
Evaporation Rate:	N/A
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity (H <sub>2</sub> O=1):	1.05
Vapor Density (air = 1):	Non-Volatile
Vapor Pressure:	N/A
VOC Content (cartridge):	0 g/L (tested per EPA CFR 40, Part 63, Subpart P, Appendix A) < 10.0 g/L (tested per ASTM E1868-10)
VOC Content (bulk):	0 g/L (tested per EPA CFR 40, Part 63, Subpart P, Appendix A) 7 g/L (tested per EPA CFR 40, Part 60, method 24)
pH:	N/D
Boiling Point:	N/A

---

**10. Stability and Reactivity (Part B)**

Stability:	Stable.
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents.
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

**11. Toxicological Information (Part B)****Acute Oral Toxicity:**  
Not Determined**Acute Dermal Toxicity:**  
Not Determined**Acute Inhalation Toxicity:**  
Not Determined**Skin Irritation:**

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Severe damage to eyes.

**Safety Data Sheet****Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Maternal Toxicity:**

Nonylphenol causes maternal toxic effects per animal testing.

**Carcinogenicity Classification:****Quartz Silica Sand (Crystalline Silica):**

IARC Group1: Known human carcinogen based on human evidence.

NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.

---

**12. Ecological Information (Part B)****Fish:**

Polyamido Amine:

Zebrafish /LC50 (96hrs) : >5.0mg/l

**Aquatic Invertebrates:**

Polyamido Amine:

Water Flea Daphnis/EC 50 (48hrs): > 7.07mg/l

**Algae:**

No Data Available

**Microorganisms:**

No Data Available

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure is the air or water will arise.

---

**13. Disposal Considerations (Part B)**

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

**14. Transportation Information (Part B)****DOT (US)**

**CARTRIDGE:** Limited Quantity, LTD QTY

**\*BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

## Safety Data Sheet

### Inject-TITE™ FS™ Fast-Set

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

\*Bulk packaging in quantities of 1.3 gallons (net) or less are packaged in accordance with the limited quantity exception.

#### IATA/ICAO

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

#### IMDG

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

## 15. Regulatory Information (Part B)

HMIS Rating	
Health	*3
Flammability	1
Physical Hazard	0
PPE	B

#### NFPA Rating



**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

#### Federal Regulations

CERCLA RQ  
5000 lbs.

CAS  
107-21-1

Chemical Name  
Ethylene Glycol (Cartridge ONLY)

SARA Title 311/312

Chronic Health Hazard

CA Prop 65

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

TSCA

Listed

#### State Regulations:

State RTK  
NJ, MA, PA

CAS#  
107-21-1  
14808-60-7  
140-31-8

Chemical Name  
Ethylene Glycol (Cartridge ONLY)  
Crystalline Silica (quartz)  
n-aminoethylpiperazine

## 16. Other Information

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard.

To the best of our knowledge, the information contained herein is accurate. However, Mechanical Plastics Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained



**HIGH-PERFORMANCE ANCHORS®**

**Safety Data Sheet**

**Inject-TITE™ FS™ Fast-Set**

Created On: 12/22/2017

Revision Date: 12/22/2017 Version: FS1217

---

herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.